



What would you do if you knew?™

Teradata Virtual Machine Community Edition

Installation, Configuration, and Upgrade Guide

Release 15.01
B035-5946-095K
September 2015

The product or products described in this book are licensed products of Teradata Corporation or its affiliates.

Teradata, Active Data Warehousing, Active Enterprise Intelligence, Applications-Within, Aprimo Marketing Studio, Aster, BYNET, Claraview, DecisionCast, Gridscale, MyCommerce, QueryGrid, SQL-MapReduce, Teradata Decision Experts, "Teradata Labs" logo, Teradata ServiceConnect, Teradata Source Experts, WebAnalyst, and Xkoto are trademarks or registered trademarks of Teradata Corporation or its affiliates in the United States and other countries.

Adaptec and SCSISelect are trademarks or registered trademarks of Adaptec, Inc.

AMD Opteron and Opteron are trademarks of Advanced Micro Devices, Inc.

Apache, Apache Avro, Apache Hadoop, Apache Hive, Hadoop, and the yellow elephant logo are either registered trademarks or trademarks of the Apache Software Foundation in the United States and/or other countries.

Apple, Mac, and OS X all are registered trademarks of Apple Inc.

Axeda is a registered trademark of Axeda Corporation. Axeda Agents, Axeda Applications, Axeda Policy Manager, Axeda Enterprise, Axeda Access, Axeda Software Management, Axeda Service, Axeda ServiceLink, and Firewall-Friendly are trademarks and Maximum Results and Maximum Support are servicemarks of Axeda Corporation.

Data Domain, EMC, PowerPath, SRDF, and Symmetrix are registered trademarks of EMC Corporation.

GoldenGate is a trademark of Oracle.

Hewlett-Packard and HP are registered trademarks of Hewlett-Packard Company.

Hortonworks, the Hortonworks logo and other Hortonworks trademarks are trademarks of Hortonworks Inc. in the United States and other countries.

Intel, Pentium, and XEON are registered trademarks of Intel Corporation.

IBM, CICS, RACF, Tivoli, and z/OS are registered trademarks of International Business Machines Corporation.

Linux is a registered trademark of Linus Torvalds.

LSI is a registered trademark of LSI Corporation.

Microsoft, Active Directory, Windows, Windows NT, and Windows Server are registered trademarks of Microsoft Corporation in the United States and other countries.

NetVault is a trademark or registered trademark of Dell Inc. in the United States and/or other countries.

Novell and SUSE are registered trademarks of Novell, Inc., in the United States and other countries.

Oracle, Java, and Solaris are registered trademarks of Oracle and/or its affiliates.

QLogic and SANbox are trademarks or registered trademarks of QLogic Corporation.

Quantum and the Quantum logo are trademarks of Quantum Corporation, registered in the U.S.A. and other countries.

Red Hat is a trademark of Red Hat, Inc., registered in the U.S. and other countries. Used under license.

SAP is the trademark or registered trademark of SAP AG in Germany and in several other countries.

SAS and SAS/C are trademarks or registered trademarks of SAS Institute Inc.

SPARC is a registered trademark of SPARC International, Inc.

Symantec, NetBackup, and VERITAS are trademarks or registered trademarks of Symantec Corporation or its affiliates in the United States and other countries.

Unicode is a registered trademark of Unicode, Inc. in the United States and other countries.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other product and company names mentioned herein may be the trademarks of their respective owners.

The information contained in this document is provided on an "as-is" basis, without warranty of any kind, either express or implied, including the implied warranties of merchantability, fitness for a particular purpose, or non-infringement. Some jurisdictions do not allow the exclusion of implied warranties, so the above exclusion may not apply to you. In no event will Teradata Corporation be liable for any indirect, direct, special, incidental, or consequential damages, including lost profits or lost savings, even if expressly advised of the possibility of such damages.

The information contained in this document may contain references or cross-references to features, functions, products, or services that are not announced or available in your country. Such references do not imply that Teradata Corporation intends to announce such features, functions, products, or services in your country. Please consult your local Teradata Corporation representative for those features, functions, products, or services available in your country.

Information contained in this document may contain technical inaccuracies or typographical errors. Information may be changed or updated without notice. Teradata Corporation may also make improvements or changes in the products or services described in this information at any time without notice.

To maintain the quality of our products and services, we would like your comments on the accuracy, clarity, organization, and value of this document. Please e-mail: teradata-books@lists.teradata.com

Any comments or materials (collectively referred to as "Feedback") sent to Teradata Corporation will be deemed non-confidential. Teradata Corporation will have no obligation of any kind with respect to Feedback and will be free to use, reproduce, disclose, exhibit, display, transform, create derivative works of, and distribute the Feedback and derivative works thereof without limitation on a royalty-free basis. Further, Teradata Corporation will be free to use any ideas, concepts, know-how, or techniques contained in such Feedback for any purpose whatsoever, including developing, manufacturing, or marketing products or services incorporating Feedback.

Copyright © 2015 by Teradata. All Rights Reserved.

Table of Contents

Preface.....	5
Purpose.....	5
Audience.....	5
Revision History.....	5
Additional Information.....	5
Related Links.....	5
Product Safety Information.....	6
<hr/>	
Chapter 1:	
Community Edition Overview.....	7
Community Edition Description.....	7
Community Edition Use Cases.....	7
<hr/>	
Chapter 2:	
Preparing for Teradata Virtual Machine Installation.....	9
Requirements.....	9
Teradata Virtual Machine Installation Components.....	9
Teradata Virtual Machine Template.....	10
Teradata Virtual Machine Property Files.....	10
Teradata Virtual Machine Scripts.....	10
Installing Teradata Virtual Machine.....	10
Specifying Administrators of a Teradata Virtual Machine Host Server.....	11
Setting PowerCLI Script Execution Privileges.....	12
Obtaining the Latest Installation Components.....	12
Editing Property Files.....	13
The vmwareit.properties File.....	13
The deploy.properties File.....	14
Unattended Deployment.....	16

Chapter 3:	
Teradata Virtual Machine Deployment.....	17
Executing the Setup Scripts.....	17
Deployment Verification.....	19
Testing the Database.....	19

Appendix A:	
Installing Teradata QueryGrid.....	21
Teradata QueryGrid Installation Overview.....	21
Teradata Database-to-Teradata Database Installation.....	21
Acquiring Remote Proxy User Information.....	21
Adding IP Addresses to the Teradata Host File.....	21
Configuring Teradata Proxy User Setup.....	22
Granting User Privileges.....	22
Creating Foreign Server Object and Accessibility.....	23
Validating the Installation.....	25
Validating the System.....	25
Teradata Database-to-Hortonworks Data Platform Installation.....	25
Acquiring Remote Proxy User Information.....	25
Identifying the HCatalog Server.....	26
Running the System Validation Script.....	26
Resolving Hostname Conflicts.....	26
Setting Up Hadoop Cluster for LDAP.....	27
Adding Hadoop IP Addresses to the Teradata Host File.....	27
Configuring Hadoop for Teradata Proxy Setup.....	28
Configuring JVM Heap Size for Teradata Database 15.0.....	29
Validating the Installation.....	30
Validating the System.....	32

Preface

Purpose

This guide contains steps to install, configure, and use Teradata Virtual Machine Community Edition (Community Edition).

To install Community Edition, you must be an experienced VMware administrator.

Audience

This guide is intended for use by:

- VMware Administrators who configure vSphere and configure and deploy Community Edition templates.
- Database and software professionals who use the deployed Community Edition instances, ensure the database is running, and use client applications to access the database for evaluation.

Revision History

Date	Description
September 2015	Initial Release.

Additional Information

Related Links

URL	Description
www.teradata.com	External site for product, service, resource, support, and other customer information.
www.info.teradata.com	External site for published Teradata customer documentation.
https://tays.teradata.com	External site for access to the Teradata software server. Accessible only with an active service contract.

Product Safety Information

This document may contain information addressing product safety practices related to data or property damage, identified by the word *Notice*. A notice indicates a situation which, if not avoided, could result in damage to property, such as equipment or data, but not related to personal injury.

Example

Notice: Improper use of the Reconfiguration utility can result in data loss.

Community Edition Overview

Community Edition Description

Community Edition is a SUSE Linux Enterprise Server (SLES) operating system and Teradata Database packaged into a virtual container that runs in a virtualized environment on third-party hardware.

Community Edition software consists of a template and associated property files and scripts.

When a Community Edition virtual machine is deployed, it operates as a fully functional instance of the configured Teradata Database.

Note: You must have administrative privileges on the destination VMware environment to install and configure Community Edition virtual machines.

Community Edition Use Cases

Once deployed by the VMware administrator, Community Edition can be used to evaluate Teradata Virtual Machine and Teradata Database.

Preparing for Teradata Virtual Machine Installation

Requirements

Community Edition has the following technical requirements.

Component	Requirements
VMware ESXi version	<ul style="list-style-type: none"> ESXi 5.5 or 6.0
Datastore space for template deployment	<ul style="list-style-type: none"> Teradata Database: 30 GB minimum
vCenter management	<ul style="list-style-type: none"> VMware administrator privileges Running vCenter Management instance (verified using the Microsoft Services control within the vCenter image) vCenter Standard version (must support ESXi 5.5 or 6.0 servers) vCenter 5.5 or 6.0
vSphere Client	<ul style="list-style-type: none"> Windows OS for vSphere Client vSphere PowerCLI version 5.5 release 2 or version 6.0
PowerCLI	<ul style="list-style-type: none"> Windows .Net Framework 4.5 Windows PowerShell V2 or latest vSphere PowerCLI toolkit

Teradata Virtual Machine Installation Components

Teradata Virtual Machine installation components consist of a template, property files, and scripts.

- The template contains the Teradata database and underlying operating system.
- Property files define configuration settings for the overall Teradata Virtual Machine environment and the specific virtual machines.
- Scripts deploy the Teradata virtual machine based on the configuration information in the property files.

Chapter 2 Preparing for Teradata Virtual Machine Installation

Teradata Virtual Machine Template

Template	Template Name	Default Configuration
Teradata Database and Operating System Template	SLES 11:	<ul style="list-style-type: none"> • 2 virtual cores • 8 GB RAM • Four 20 GB virtual data disks • 1 network adapter
	• TVME-TD15.00__SLES11_ESXi.15.00.xx.xx-1	
	• TVME-TD14.10__SLES11_ESXi.14.10.xx.xx-1	
	SLES 10:	
	• TVME-TD15.00__SLES10_ESXi.15.00.xx.xx-1	
	• TVME-TD14.10__SLES10_ESXi.14.10.xx.xx-1	

Teradata Virtual Machine Property Files

Properties File Name	Contents
<code>vmwareit.properties</code>	Virtual environment configuration settings common across Teradata virtual machines. Define the values in this file once, unless something in the virtual environment changes.
<code>deploy.properties</code>	Configuration settings unique to the Teradata virtual machine. Define the values in this file for each deployment.

Teradata Virtual Machine Scripts

Script	Description
<code>deploy.ps1</code>	Parses the <code>vmwareit.properties</code> and <code>deploy.properties</code> files to ensure that all required values are present and correctly formatted, validates settings, and launches each subsequent script to deploy the components of the Teradata virtual machine.
<code>TVMCEDeployAndConfigureDBS.ps1</code>	Deploys the Teradata Database and underlying operating system for the Teradata virtual machine.

Installing Teradata Virtual Machine

You must be a VMWare administrator to install and configure Teradata Virtual Machine software.

- 1 Log on to [Teradata Developer Exchange Downloads](#).
- 2 [Download and save the Community Edition templates and scripts](#).
- 3 [If applicable, limit administration of the Teradata Virtual Machines host server to certain users](#).

- 4 [Set PowerCLI Script execution privileges.](#)
- 5 [Edit the `vmwareit.properties` file.](#)
- 6 [Edit the `deploy.properties` file with the values for the specific Teradata Virtual Machine installation.](#)
- 7 [Run the setup script to install the Teradata virtual machine.](#)
- 8 [Confirm that the Teradata Database installed correctly.](#)
- 9 [If you plan to use Teradata QueryGrid, configure the connector.](#)

Specifying Administrators of a Teradata Virtual Machine Host Server

To allow only certain users to administer a Teradata Virtual Machine host server in a shared virtual environment, add those users as administrators of a datacenter containing the server.

- 1 Open vSphere Client.
- 2 Log in to the vCenter Server associated with the Teradata Virtual Machine host server.
- 3 In the tree view, right-click the vCenter Server listing, and select New Datacenter.
- 4 In the tree view, click New Datacenter, and rename it as appropriate.
- 5 Add the ESXi server that will host the Teradata virtual machines to the new datacenter:
 - a In the tree view, right-click the datacenter branch, and select Add Host.

The screenshot shows the 'Add Host' wizard in vSphere Client. It is divided into two main sections: 'Connection' and 'Authorization'. The 'Connection' section contains a text input field for 'Host' with a placeholder text 'Enter the name or IP address of the host to add to vCenter.' The 'Authorization' section contains two input fields for 'Username' and 'Password' with a placeholder text 'Enter the administrative account information for the host. vSphere Client will use this information to connect to the host and establish a permanent account for its operations.'

- b At Host, enter the name or IP address of the ESXi host.
- c At Authorization, enter the username and password, and click Next.
- d If an authenticity message appears, click Yes to continue.
- e At Host Summary, click Next.
- f At Assign License, ensure that the Essentials license is selected, and click Next.

- g Click Next through the remaining prompts, then click Finish.

The host name appears in the tree view, under the datacenter branch.

- 6 In the tree view, click the branch for the datacenter containing the Teradata Virtual Machine host server.

- 7 Click the Permissions tab.

- 8 In a blank area of the tab, right-click, then select Add Permission.

The Assign Permissions window appears.

- 9 Under Assigned Role, select Administrator.

- 10 Under Users and Groups, click Add.

The Select Users and Groups window appears.

- 11 From the Domain list, select the Active Directory where the accounts for the users who you want to designate as administrators exist.

- 12 In the list pane, select the applicable users or groups.

- 13 Click Add.

- 14 When you have finished selecting users or groups, click OK.

The Select Users and Groups window closes, and the Permissions tab reflects the selected users or groups.

Setting PowerCLI Script Execution Privileges

If this is a new installation of PowerCLI, you must set the PowerCLI script execution privileges to allow the unsigned but Teradata-certified Teradata Virtual Machine scripts to be run.

- 1 In a PowerCLI command window, run: `Set-ExecutionPolicy -ExecutionPolicy unrestricted`
- 2 If you are prompted to confirm the change, enter `y`.

Obtaining the Latest Installation Components

Before installing Teradata Virtual Machine, download the latest templates, property files, and scripts from Teradata Developer Exchange.

- 1 Log on to Developer's Exchange: [Teradata Developer Exchange Downloads](#)
- 2 Under Display Downloads From, select Database.
- 3 In the download list, select Community Edition, and download the `CommunityEdition.rar` and `Template.rar` files.

- 4 Decompress the downloaded .rar files.

Editing Property Files

Edit the `vmwareit.properties` file only once unless something in your virtual environment changes. Edit the `deploy.properties` file before deploying each Teradata virtual machine.

- 1 In a text editor, open the properties file you need to edit.

The files are in `/CommunityEdition/`.

- 2 Update the file as needed.

- 3 Save the file.

Related Topics

[The `vmwareit.properties` File, on page 13](#)

[The `deploy.properties` File, on page 14](#)

The `vmwareit.properties` File

The `vmwareit.properties` file contains the VMware vSphere environment and IT configuration settings common to every Teradata virtual machine deployment.

Configure the values in the `vmwareit.properties` file only once unless something in the virtual environment changes.

Property Category	Properties	Description
VMWare Details	<code>vCenterServerNameOrIPAddress</code>	The name or IP Address of the vCenter server. Example: <code>vCenterServerNameOrIPAddress=192.168.0.0</code>
vCenter Server Credentials	<code>vCenterServerUserName</code> <code>vCenterServerPassword</code>	Credentials required if you want to use the <code>-force</code> option for unattended deployment; otherwise, you must manually provide the credentials when prompted during deployment. Example: <code>vCenterServerUserName=Admin</code> <code>vCenterServerPassword=Password</code>
Common Network Details	<code>NetworkDomain</code> <code>NetworkPrimaryDns</code> <code>NetworkSecondaryDns</code>	The network domain and primary DNS (both required) and the secondary DNS (optional). Example: <code>NetworkDomain=corp.company.com</code>

Chapter 2 Preparing for Teradata Virtual Machine Installation

Property Category	Properties	Description
		<pre>NetworkPrimaryDns=192.168.0.1 NetworkSecondaryDns=192.168.0.2</pre>
Network Switch vSwitch0	VirtualNetworkPortGroupName	<p>The physical adapter with port group for the virtual network. The default value is VM Network.</p> <p>Example:</p> <pre>VirtualNetworkPortGroupName=VM Network</pre>

The deploy.properties File

The `deploy.properties` file contains the specifications needed by the deployment scripts to install and configure a given Teradata Database virtual machine.

Set the values in the `deploy.properties` file for each Teradata Virtual Machine deployment.

Property Category	Properties	Description
VMWare Host Details	ESXiHostName	<p>Name of the VMware host on which the virtual machine will run.</p> <p>Example:</p> <pre>ESXiHostName=esxhost01.corp.company.com</pre>
Datastore	Datastore	<p>Datastore associated with the host.</p> <p>Example:</p> <pre>Datastore=datastore001-vol01</pre>
VMWare Template Details	DeployDBSOVFTemplate DatabaseOVFFilePath ExistingDBSTemplateName	<p>Source of the template for the virtual machine being deployed in the specified VMWare environment.</p> <p>To use an OVF template from your local computer, set <code>DeployDBSOVFTemplate</code> to <code>true</code> and specify the <code>DatabaseOVFFilePath</code> value.</p> <p>Example:</p> <pre>DeployDBSOVFTemplate=true DatabaseOVFFilePath=C:\\TVME\\TVME- TD15.00__SLES10_ESXi.15.00.02.02-1.ovf</pre> <p>To use a template that was previously loaded to the vCenter environment, set <code>DeployDBSOVFTemplate</code> to <code>false</code> and specify the <code>ExistingDBSTemplateName</code> value.</p> <p>Example:</p> <pre>DeployDBSOVFTemplate=false ExistingDBSTemplateName=TVME- TD15.00__SLES11_ESXi.15.00.03.05-1</pre>

Property Category	Properties	Description
VM Name and Location	DbsVMName	The name of the virtual machine and the folder to which it should be deployed in the VMware environment. Examples: DbsVMName=TVME-CE1 Location=FolderName
	LocationName	
DBS Configuration	NumberOfDataDisks	Total number of data disks and size of each data disk. The number of data disks must be even, and the data disk size must be an increment of 10 GB. The maximum database size (NumberOfDataDisks X DataDiskSizeGB) is 1024 GB. Examples: NumberOfDataDisks=4 DataDiskSizeGB=20
	DataDiskSizeGB	
VM Configuration	NumCPU	Number of CPUs and amount of memory. Allocate at least 2 GB of memory for each data disk. Examples: NumCPU=2 MemoryGB=8
	MemoryGB	
DBSControl Flags	Temporal	Database features, enabled by setting the value to true. Accept the default of false if you do not plan to use the feature. Note: If you plan to enable Temporal and restore data from a different Teradata Database, review Knowledge Article KAP1BACEE , <i>Migrating to TimeDateWZControl</i> first. This scenario can result in subtle data quality issues which are outlined in the Knowledge Article. If enabling QueryGrid, also specify the QueryGridVersion value. For Teradata Database version 14.10, use SQLH instead of QueryGrid for this feature, and do not specify the QueryGridVersion value. Note: QueryGrid is supported for HDP 1.3 and 2.1 versions.
	Columnar	
	BlockLevelCompression	
	RowLevelSecurity	
	SQLH	
	QueryGrid	
	QueryGridVersion	
Static IP Address and Host Name for Database VM	IPAddressSetting	The IP address setting and the host name, IP address, subnet mask, and network gateway for the Teradata Database virtual machine. <ul style="list-style-type: none"> The default host name is TVME-CE. If IPAddressSetting=dhcp (the default), only the HostNameForDbsVM property value is required; if IPAddressSetting=static, all other property values are required. The subnetmask value must be in the format of XXX.XXX.XXX.X. Examples:
	HostNameForDbsVM	
	IPAddressForDbsVM	
	SubnetmaskForDbsVM	
	NetworkGatewayForDbsVM	

Property Category	Properties	Description
		<code>IPAddressSetting=static</code> <code>HostNameForDbsVM=TVME-CE</code> <code>IPAddressForDbsVM=192.168.0.10</code> <code>SubnetmaskForDbsVM=255.255.254.0</code> <code>NetworkGatewayForDbsVM=192.168.1.254</code>

Unattended Deployment

Teradata Virtual Machine allows unattended deployment using a command line parameter. The unattended deployment uses login credentials provided in the `vmwareit.properties` file, and assumes the default response to each prompt normally shown during deployment.

To deploy Teradata Virtual Machine without manual intervention:

- Specify the vCenter login credentials in the `vmwareit.properties` file.
- Configure the other values in the `vmwareit.properties` and `deploy.properties` files.
- Run the deployment script with a `-force` parameter.

Teradata Virtual Machine Deployment

Executing the Setup Scripts

The start-up script, `deploy.ps1`, verifies that all required property file values are present and correctly formatted, and validates other settings. If it finds no errors, the script deploys the virtual machine.

If you use the `-force` parameter, the script runs unattended. See [Unattended Deployment](#) for more information.

- 1 Open the PowerCLI console.
- 2 Change the directory to the location where the downloaded Teradata Virtual Machine installation files are stored.
- 3 Run the `deploy.ps1` script:

```
.\deploy.ps1 -vmFile vmwareit.properties -tvmeFile  
deploy.properties
```

Note: For unattended deployment, use the `-force` parameter: `.\deploy.ps1 -force -vmFile vmwareit.properties -tvmeFile deploy.properties`

The script validates all the entries in the `vmwareit.properties` and `deploy.properties` files.

```

=====
TUM Community Edition DBS VM Deploy and Configuration Version:15.01.00.00
=====
vCenter IP address/Name      : vCenter1.corp.company.com
ESXi Host                    : esxHost1.corp.company.com
Datastore                    : eqlgrptome001-vol01
Template Name                 : TUME-TD15.00__SLES11_ESXi.15.00.
03.05-1
New VM Name                   : TUME-CE1
Folder                       :
Number Of Data Disks         : 4
Data Disk Size <GB>          : 20
Memory <GB>                  : 8
Number Of CPUs                : 2
IP address scheme            : dhcp
Database VM HostName         : TUME-CE1
Network Domain                : corp.company.com
Primary DNS                   : 192.64.1.200
Secondary DNS                  : 192.65.1.10
Virtual Network PortGroup Name : UM Network
Enable Temporal                : false
Enable Columnar                : false
Enable BlockLevelCompression   : false
Enable Row Level Security       : false
Enable SQLH                     : false
Enable QueryGrid               : false
=====
If the above information is correct, press <y> to deploy virtual machine....:

```

- 4 Review the information. If it is correct, press *y*.

If the information is not correct, edit the property files and re-run the script.

The system prompts you to log on to the vCenter server.

- 5 Type your vCenter User name and Password, then click OK.

The script connects to the vCenter server and validates the information in the property files.

When validation is successful, the script deploys the selected template, and configures the virtual machine based on the values in the property files.

- 6 If a message warns you that running scripts is disabled, you must set the script execution privileges, then re-run the script.

See [Setting PowerCLI Script Execution Privileges](#).

Deployment Verification

After a Teradata Virtual Machine deployment, test the Teradata Database.

Testing the Database

After a Teradata Virtual Machine deployment, verify that the database is accessible and responsive.

- 1 Start BTEQ.
- 2 Using the default credentials, log in to the database.
- 3 Run `select * from dbc.dbcinfo` to see if the database is responding.

Sample result indicating response:

```

sel * from dbc.dbcinfo;

*** Query completed. 3 rows found. 2 columns returned.
*** Total elapsed time was 1 second.

InfoKey          InfoData
-----
VERSION          15.00.01.01
RELEASE          15.00.01.01
LANGUAGE SUPPORT MODE Standard

```

- 4 If the database does not respond, try to access the server through SSH.
- 5 If you cannot access the server, contact Teradata Customer Service.

Chapter 3 Teradata Virtual Machine Deployment

Installing Teradata QueryGrid

Teradata QueryGrid Installation Overview

If you configured a Teradata virtual machine to enable the Teradata QueryGrid feature, you must take additional steps to complete installation of the feature after deploying the virtual machine. The steps differ depending on the version of Teradata QueryGrid you are using. Supported versions are as follows:

- Teradata Database-to-Teradata Database (TD-to-TD)
- Teradata Database-to-Hortonworks Data Platform (TD-to-HDP)

Teradata Database-to-Teradata Database Installation

To complete installation of the TD-to-TD version of Teradata QueryGrid on a virtual machine, perform the outlined procedures in order.

Acquiring Remote Proxy User Information

When installing Teradata QueryGrid Teradata Database-to-Teradata Database, a Teradata proxy user must be configured. The proxy user is the user used to log on between Teradata systems and impersonates the local user on the remote Teradata Database system.

For configurations with Teradata Database-to-Teradata Database on both local and remote Teradata systems, it is recommended that a unique proxy user be created for systems in both sides of the configuration.

- 1 Confirm the proxy user values have been provided.

Adding IP Addresses to the Teradata Host File

Resolve all hostname conflicts and confirm the hostnames are not being resolved through a local DNS.

- 1 On all Teradata TPA nodes, save a copy of the `/etc/hosts` file at:
`cp /etc/hosts/etc/orig.hosts`
- 2 Add the Teradata TPA nodes IP addresses to `/etc/hosts`.
For example:

Appendix A Installing Teradata QueryGrid

- 192.168.135.100 node002-8
- 192.168.135.101 node002-9

Configuring Teradata Proxy User Setup

For configurations where TD-to-TD is desired on both the local and remote Teradata systems, a unique proxy user name for each system is recommended.

The proxy user usually has no perm space or permissions beyond acting as proxy. However, the user may require SPOOL and TEMPORARY space based the specific query workload of all users of the remote server. Adjust as appropriate.

- 1 Confirm the remote proxy user exists.
- 2 On the remote Teradata Database system, log in as Administrator.
For example, log in as user *dbc*.
- 3 Run the following query:

```
CREATE USER proxyuser AS PERM = 0 PASSWORD = password;
```

Granting User Privileges

The Teradata Database user requires specific privileges to run the installation setup. These privileges can be granted by the database administrator. If the administrative user is not known, use *dbc*.

Note: GRANT statements are not required if using an administrator such as *dbc* to run the setup.

- 1 Grant the execute procedure on SQLJ:

```
GRANT EXECUTE PROCEDURE ON SQLJ TO user WITH GRANT OPTION;
```
- 2 Grant the create procedure on SYSLIB to user:

```
GRANT CREATE PROCEDURE ON SYSLIB TO user WITH GRANT OPTION;
```
- 3 Grant the create external procedure on SYSLIB:

```
GRANT CREATE EXTERNAL PROCEDURE ON SYSLIB TO user WITH GRANT OPTION;
```
- 4 Grant the drop procedure on SYSLIB:

```
GRANT DROP PROCEDURE ON SYSLIB TO user WITH GRANT OPTION;
```
- 5 Grant the drop function on SYSLIB:

```
GRANT DROP FUNCTION ON SYSLIB TO user WITH GRANT OPTION;
```
- 6 Grant the execute function on SYSLIB:

```
GRANT EXECUTE FUNCTION ON SYSLIB TO user WITH GRANT OPTION;
```
- 7 Grant the create function on SYSLIB:

```
GRANT CREATE FUNCTION ON SYSLIB TO user WITH GRANT OPTION;
```
- 8 Grant select on SYSLIB:

```
GRANT SELECT ON SYSLIB TO user WITH GRANT OPTION;
```

9 **Grant all on user to user:**

```
GRANT ALL ON user TO user, dbc WITH GRANT OPTION;
```

10 **Grant UDTTYPE on SYSUDTLIB:**

```
GRANT UDTTYPE ON SYSUDTLIB TO user WITH GRANT OPTION;
```

11 **Grant the create external procedure on TD_SERVER_DB:**

```
GRANT CREATE EXTERNAL PROCEDURE ON TD_SERVER_DB TO user WITH GRANT OPTION;
```

12 **Grant the drop procedure on TD_SERVER_DB:**

```
GRANT DROP PROCEDURE ON TD_SERVER_DB TO user WITH GRANT OPTION;
```

13 **Grant the execute function on TD_SERVER_DB:**

```
GRANT EXECUTE FUNCTION ON TD_SERVER_DB TO user WITH GRANT OPTION;
```

14 **Grant the create function on TD_SERVER_DB:**

```
GRANT CREATE FUNCTION ON TD_SERVER_DB TO user WITH GRANT OPTION;
```

15 **Grant select on TD_SERVER_DB:**

```
GRANT SELECT ON TD_SERVER_DB TO user WITH GRANT OPTION;
```

16 **Grant create server on TD_SERVER_DB:**

```
GRANT CREATE SERVER ON TD_SERVER_DB TO user WITH GRANT OPTION;
```

17 **Grant drop server on TD_SERVER_DB:**

```
GRANT DROP SERVER ON TD_SERVER_DB TO user WITH GRANT OPTION;
```

18 **Grant insert on TD_SERVER_DB:**

```
GRANT INSERT ON TD_SERVER_DB TO user WITH GRANT OPTION;
```

19 **Grant select on TD_SERVER_DB to SYSLIB:**

```
GRANT SELECT ON TD_SERVER_DB TO SYSLIB;
```

Creating Foreign Server Object and Accessibility

This procedure defines the remote server and sets accessibility to users on the local system. Perform all steps on the local Teradata Database.

Use this procedure for installations and when creating new remote servers or access. Do not use for upgrades.

1 **Grant the proxy user privileges for all users to be impersonated:**

```
GRANT CONNECT THROUGH proxyuser TO PERMANENT local_user without role;
```

2 **Create an authorization object for the remote server:**

```
CREATE AUTHORIZATION td_server_db.remote_server_hostnameproxy AS  
DEFINER TRUSTED USER 'proxyuser' PASSWORD 'password';
```

This creates the proxy in the `td_server_db` database. The *DEFINER* clause is used to make this global to all users.

- 3 Log into the local Teradata system and grant DBC access to create server objects in the name of the remote system:

```
GRANT CREATE SERVER ON td_server_db TO dbc;
```

- 4 Create the server:

```
CREATE FOREIGN SERVER <remote_server_hostname>
EXTERNAL SECURITY DEFINER TRUSTED <remote_server_hostname>proxy
USING
Hosttype('Teradata')
remotehost ('<remote_server_hostname>.<FQDN>')
local_ips('<local_server_hostname>.<FQDN>')
port('5000')
```

Note: Ensure the port is open. The port must be open for validating.

```
read_timeout(200)
listen_timeout(60)
concurrentstreams(1)
DO IMPORT WITH syslib.load_from_td,
DO EXPORT WITH syslib.load_to_td;
```

For example:

```
CREATE FOREIGN SERVER sd117151
EXTERNAL SECURITY  DEFINER TRUSTED sd117151proxy
  USING
  Hosttype('Teradata')
  remotehost ('sd117151.labs.teradata.com')
  local_ips('sd1c0062.labs.teradata.com')
  port('5000')
  read_timeout(200)
  listen_timeout(60)
  concurrentstreams(1)
  DO IMPORT WITH syslib.load_from_td,
  DO EXPORT WITH syslib.load_to_td;
```

- 5 From database `td_server_db`., grant *SELECT* and *INSERT* on the remote server to local users.

```
GRANT SELECT ON remote_server_hostname to local user;
GRANT INSERT ON remote_server_hostname to local user;
```

For example:

```
GRANT SELECT ON sd117151 to sd1c_user2;
GRANT INSERT ON sd117151 to sd1c_user2;
```


Validating the Installation

Verify that the proxy user is setup.

- 1 Log into the local Teradata Database as a local user.
- 2 To validate the installation run the Help Foreign Server query:
HELP FOREIGN SERVER remote_server_hostname;

Validating the System

Validate the local and remote nodes.

- 1 On the local and remote nodes configured for Teradata Query Grid:
`/opt/teradata/gsctools/bin/chk_all`
- 2 Review the output and confirm it is correct:
`/var/opt/teradata/gsctools/chk_all`

Teradata Database-to-Hortonworks Data Platform Installation

To complete installation of the TD-to-HDP version of Teradata QueryGrid on a virtual machine, perform the outlined procedures in order.

Acquiring Remote Proxy User Information

This topic applies to versions of Teradata-to-Hadoop prior to Teradata 15.00.02. The Hadoop administrator usually performs this procedure.

For Teradata QueryGrid to work with a Hadoop system, a Teradata proxy user must be configured on the Hadoop NameNode. This proxy user must be allowed to access HDFS from the Teradata nodes on behalf of another Hadoop user in a secured way. The Teradata proxy user for this setting is *tdatuser*.

- 1 Confirm the following:
 - The proxy user values have been provided.
 - Both *tdatuser* and the *tdatuser* home directory exist in `/home`.
For example: `/home/tdatuser`
 - The default shell for the user is set to `/etc/passwd`.
For example: `/bin/bash`
- 2 On the Hadoop side, the following configurations are required in `core-site.xml` to add *tdatuser* as a trusted proxy user:
 - a Determine the file system groups that *tdatuser* may impersonate.

Appendix A Installing Teradata QueryGrid

- b Determine the hosts and nodes from where the *tdatuser* user may access the HDFS. These configurations must be present, otherwise impersonation is not allowed and Teradata queries fail with a security error.

Identifying the HCatalog Server

All nodes in the Hadoop cluster must have the HCatalog libraries installed. HCatalog is the entry point for the Teradata QueryGrid connector.

- 1 If the customer has changed the default Ambari server login credentials of *admin/admin*, obtain the new updated credentials.
- 2 Log onto Ambari on a Hadoop node:
 - For TDH systems, use port 8081.
 - For HDP systems, use port 8080.
 If an external connection already exists, use SWS through Server Management or the customer name.
- 3 Click the Hive tab.
- 4 Click **Configs**.
The Hive Metastore host is displayed.

Running the System Validation Script

After identifying the HCatalog Server, run the system validation script.

- 1 Save `sys_val.pl` to the `/home/support` directory on both the Teradata and Hadoop nodes.
- 2 Verify the system by running `sys_val.pl` on both the Teradata control and PDN nodes and Hadoop master node.

`sys_val.pl` should be run separately and independently on both types of systems.

Description	Command
Teradata Control or PDN nodes and Hadoop Master nodes	<code>/home/support/sys_val.pl -cc</code>
Scripts with CR/LF, binary FTP from Windows	<code>perl /home/support/sys_val.pl -cc</code>

Resolving Hostname Conflicts

Teradata-to-Hadoop uses node hostnames to resolve network addressing. However, it is possible that there may be conflicts and duplicate hostnames between Teradata nodes and Hadoop nodes that must be resolved before Teradata QueryGrid is installed.

If problems exist, contact the Teradata Global Support Center, Hadoop Support team for changes.

Setting Up Hadoop Cluster for LDAP

Before using Teradata QueryGrid with LDAP, update the storage format in the LDAP directory.

Note: `tdsqlh_td 15.00.02.01` is the minimum version of the Teradata QueryGrid connector package required to use with LDAP.

- 1 In Ambari, open the Hive configuration page.
- 2 Complete the fields:

hive.server2	Description
hive.server2.authentication	LDAP
hive.server2.authentication.ldap.base DN	Matches the directory location where the authenticated users are stored on the LDAP server
hive.server2.authentication.ldap.url	Matches the correct LDAP server

Note: HiveServer2 requires the schema for user Distinguished Names (DN) to follow the format `uid=<username>,baseDN` where:

- *username* is the name of the user being added
- *baseDN* is the directory where the authenticated usernames are stored

For example:

The screenshot shows the Ambari configuration interface for Hive. It displays three configuration fields for the 'hive.server2.authentication' property:

- hive.server2.authentication:** Set to 'LDAP'. It has 'Override' and 'Remove' buttons.
- hive.server2.authentication.ldap.baseDN:** Set to 'OU=Users,DC=TD,DC=TERADATA,DC=COM'. It has 'Override' and 'Remove' buttons.
- hive.server2.authentication.ldap.url:** Set to 'ldap://sdlc1616/'. It has 'Override' and 'Remove' buttons.

- 3 Save the changes and restart all Hive services.

Adding Hadoop IP Addresses to the Teradata Host File

Resolve all hostname conflicts and confirm the hostnames are not being resolved through a local DNS.

- 1 On all Teradata TPA nodes, save a copy of the `/etc/hosts` file at:

```
cp /etc/hosts/etc/orig.hosts
```
- 2 Add the Hadoop node's IP addresses to `/etc/hosts`.
 For example:
 - `192.168.135.100 hdp002-8`
 - `192.168.135.101 hdp002-9`
- 3 Confirm the `byn1` IP addresses on Hadoop systems using `byn1`.

Configuring Hadoop for Teradata Proxy Setup

The method used to configure the Teradata proxy user on the Hadoop NameNode is determined by the Hadoop system version.

Configuring Hadoop for Teradata Proxy Setup for Hadoop 2.1 Systems Using Ambari

Note: This topic applies to versions of Teradata-to-Hadoop prior to Teradata 15.00.02.

Use Ambari to edit the `core-site.xml` file. Note the following:

- Property value changes made in Ambari appear in the `core-site.xml` file.
- Property value changes made in `core-site.xml` through manual editing do not appear in Ambari.

If Ambari is used for cluster management, then also use Ambari for modifying service property values.

- 1 Verify the customer has provided the following information needed for the configuration.
 - Ambari server login and password
The default Ambari server username and password is *admin/admin*. If the customer has changed the Ambari server password, it must be provided prior to the installation.
 - Network access to Hadoop Master Node 1
 - The values to complete the Add Property field have been obtained

- 2 Log onto Ambari Hadoop Master Node 1:

- For TDH systems, use port 8081.
- For HDP systems, use port 8080.

Use SWS through Server Management or customer name if external connections already exist.

For example, for HDP systems, use `http://hdp002-1:8080` and for TDH systems, use `http://hdp002-1:8081`

- 3 Click the Services tab.
- 4 From the left pane, click HDFS.
- 5 On the HDFS screen, click the **Configs** tab.
- 6 Expand Custom `core-site.xml`.
- 7 Configure the Teradata proxy user:

The default wildcard value for these properties is `*` and allows impersonation from any host or user. If specific groups and hosts have been identified, replace `*` with the groups and hosts in a comma separated list.

- a Click Add Property and add a property with the key value `hadoop.proxyuser.tdatuser.groups` and value `*`.
- b Click Add Property and add a property with the key value `hadoop.proxyuser.tdatuser.hosts` and value `*`.

- 8 Click Save.
- 9 When the Restart button appears, restart HDFS by clicking Restart > Restart All > **Confirm Restart All**.

Configuring Hadoop for Teradata Proxy Setup for Hadoop 1.3.2 Systems

Note: This topic applies to versions of Teradata-to-Hadoop prior to Teradata 15.00.02.

For Hadoop 1.3.2 systems, Ambari is disabled and you must edit the `core-site.xml` file manually.

- 1 Navigate to the Hadoop NameNode configuration file:
`/etc/hadoop/conf/core-site.xml`
- 2 Add the following properties to the file: and properties to the file.
 - `hadoop.proxyuser.tdatuser.groups`
 - `hadoop.proxyuser.tdatuser.hosts`

```
<property>
  <name>hadoop.proxyuser.tdatuser.groups</name>
  <value>users</value>
  <description>
    Allow the proxy user tdatuser to impersonate any members of
    HDFS group(s). For example, 'users' is used as HDFS group that
    tdatuser is allowed to impersonate users belonged to this group.
  </description>
</property>

<property>
  <name>hadoop.proxyuser.tdatuser.hosts</name>
  <value>host1,host2</value>
  <description>
    The proxy user can connect only from host1 and host2 to
    impersonate a user. Here host1 and host2 represents Teradata nodes.
    All nodes of the Teradata system need to be listed here in order
    for SQL-H query to be processed. It is recommended to use the IP
    addresses of the Teradata nodes.
  </description>
</property>
```

The property values are based on the Teradata and Hadoop environment setup requirements.

- 3 Save the `core-site.xml` file.
- 4 Restart the NameNode:


```
hcli system restart
```

Configuring JVM Heap Size for Teradata Database 15.0

This procedure applies only to Teradata Database 15.00 installations.

Appendix A Installing Teradata QueryGrid

cufconfig was enhanced for Teradata QueryGrid 15.0. A new option, `JVMOptions`, was added so that the environment file does not have to be placed on all nodes. The options needed can be added using `cufconfig` and are automatically replicated to all nodes.

- 1 If upgrading, before beginning the upgrade process remove any existing JVM options:
 - a On the primary Teradata node, edit `/tmp/jvm_base.txt` by removing `/tmp/jvmopt.txt` from the `JavaEnvFile` field.
 - b Run `cufconfig -f /tmp/jvm_base.txt`.
 - c Run `cufconfig -o`.
The `JavaEnvFile` field value must be empty.
- 2 Calculate the Java Heap values.
To do the memory calculations, see Knowledge Article: [KAP3160E8E](#), *Teradata QueryGrid Teradata Database-to-Hadoop Orange Book*.
- 3 In the `/tmp` directory of the primary Teradata node, create a new `jvmopt.txt` file with the following options:


```
JVMOptions: -server -XX:UseParallelGC -XX:+UseParallelOldGC -Xms7100m -Xmx7100m -XX:NewSize=2370m -XX:MaxNewSize=2370m -XX:MaxPermSize=864m
```
- 4 Set the `jvmopt.txt` file permissions:


```
psh chmod 777 /tmp/jvmopt.txt
```
- 5 Run `cufconfig -f /tmp/jvmopt.txt`.
- 6 Run `cufconfig -o`
The `JVMOptions` field value must be populated.
- 7 Restart the Teradata Database:


```
tpareset -y restart-with-sqlh
```

Validating the Installation

Validate the Teradata and Hadoop setups are ready for Teradata-to-Hadoop queries.

- 1 Create the `hcatalog` table with data:
 - a On the primary Teradata node, navigate to `/opt/teradata/sqlh/version`.
 - b Download `tdsqlh_example.hive` and `tdsql_data.csv` and copy them to the `/tmp` directory on the Hadoop NameNode.
 - c Log into the Hadoop NameNode and navigate to the `/tmp` directory.
 - d Change files permissions on the copied files:


```
chmod 777 tdsqlh_example.hive tdsql_data.csv
```
 - e Change the user to *Hive*:


```
su hive
```

- 2 Run a sample Hive script by creating a `tdsqlh_test` table with 14 columns and 805 populated rows:

```
hive < tdsqhlh_example.hive
```

Verify the script completes and returns row count as 805.

```
Total MapReduce CPU Time Spent: 4 seconds 580 msec
OK
805
Time taken: 33.76 seconds
```

- 3 Use SQL Assistant or BTEQ to log into the Teradata primary node as user `dbc`.
- 4 Run the Teradata-to-Hadoop query to import rows from the `tdsqlh_test` table. Use the following values:
- 5 Run the query to count the rows in the `tdsqlh_test` table. If the server hostname is unknown, look in the `/etc/hosts` file.
 - For TDH systems, (`'hdp001-hive'`) is used in the following example to specify the server. TDH systems use the Hive VIP when specifying the server.
 - For HDP systems, (`'hdp001-1'`) is used in the following example to specify the server. HDP systems use the hostname of the master node when specifying the server.

For Hadoop 2.1 systems with one master node and Hadoop 1.3.2 systems, run the following SQL query:

```
SELECT count(*)
FROM SYSLIB.load_from_hcatalog(USING
  server('hdp001-hive') or ('hdp001-1')
  port('9083')
  username('hive')
  dbname('default')
  tablename('tdsqlh_test')
  columns('*')
  templeton_port('50111')

hadoop_properties('dfs.client.use.datanode.hostname=
true')
) as D1;
```

For Hadoop 2.1 systems with two or more master nodes, make the required replacements, then run the following SQL query:

- Replace the `dfs.nameservices` name ("YOURCLUSTER" in the example) with the defined cluster name.
- Replace the `dfs.namenode.rpc-addresses` ("NAMENODE1" and

```
SELECT count(*)
FROM SYSLIB.load_from_hcatalog(USING
  server('hdp001-hive') or ('hdp001-1')
  port('9083')
  username('hive')
  dbname('default')
  tablename('tdsqlh_test')
  columns('*')
  templeton_port('50111')

hadoop_properties('<dfs.client.use.datanode.hostname=
true>,
<dfs.datanode.use.datanode.hostname=true>,
<dfs.nameservices=<YOURCLUSTER>,
<dfs.ha.namenodes.YOURCLUSTER=nn1,nn2>,
<dfs.namenode.rpc-
address.YOURCLUSTER.nn1=NAMENODE1:8020>,'
```

Appendix A Installing Teradata QueryGrid

"NAMENODE2" in the example) with the defined addresses.

```
<dfs.namenode.rpc-  
address.YOURCLUSTER.nn2=NAMENODE2:8020>,  
<dfs.client.failover.proxy.provider.YOURCLUSTER=o  
rg.apache.hadoop.hdfs.server.namenode.ha.Configur  
edFailoverProxyProvider>')  
) AS D1;
```

Clustername and namenode rpc-addresses are located in the `hdfs-site.xml` settings:
Services > HDFS > **Configs** > Custom `hdfs-site.xml`

The following are common terms found in this script:

Term	Definition
Server	DNS hostname or IP address for the Hadoop NameNode
Port	Port for the Hadoop NameNode service
templeton_port	The web Hcatalog port

If the query returns an error instead of row count 805 then the Teradata-to-Hadoop setup requires manual troubleshooting to isolate the problem.

Validating the System

- 1 To verify the system, independently run the following on both the Teradata Control/PDN node and Hadoop master node:

`sys_val.pl`

Description	Command
Teradata Control or PDN nodes and Hadoop Master nodes	<code>/home/support/sys_val.pl -cc</code>
Scripts with CR/LF, binary FTP from Windows	<code>perl /home/support/sys_val.pl -cc</code>